

We have different kind of light bulbs to use on all digital imaging needs



SB-28
5200K daylight fluorescent, spiral bulb, 28W, with E-27 screw base. It is an energy saver bulb, very good color for digital capture. It has built-in electronic ballast, average usable life for imaging is 8000 hours. 1650 lumens. equals to 130w incandescent bulb. UL/CSA/CE approved. Works on our FL-360, FL-750, Q-26, Q-30 and Q-40 reflectors.



SB-85
The SB-85 fluorescent bulb is a rugged light bulb. It has 5200K daylight quality light. It delivers *6000/ft lumens equals 550W of incandescent bulb but without the heat. It rates for 8000 hours. CRI value is 82.*with proper reflector on.



MH-150W
5200K daylight Metal Halide bulb. Double envelope with E-27 screw base. Average life is 7000 hours. Works only on our MH-Imager lampheads equipped with electronic ballasts. 12500 lumens. 150W equals to 800W incandescent bulb. Diffusion coating is in outer glass. As it is a high pressure gas arc bulb, and is the most efficient of all constant light bulbs that convert electricity to light. Use with caution, needs proper protective shield as it is externally hot in inner glass envelope which contains high pressure gas. CE approved.



BB3RD-FT
Replacement flash tube for Digital Barebulb.



ZX1052
Ring flash tube for Hybrid, QF-Imager



XFT-001-01U
Half circle flash tube for Flasi-imager, needs two to form a ring in one unit.

Ultra bright, 3200K, 1000w quartz halogen bulb, double envelope with tungsten filament. Average life is 100 hours, fits on E-40 screw base ceramic socket. Works on H-1000 lamphead.



JTT1000



PL-27W
5500K double fluorescent tube, 27W, ultra bright. It is to fit on our FL-500 light panel. Light output equals to 170W incandescent bulb.



PL-27BL/120 or 230
Replacement electronic ballast for PL-27W fluorescent tube. Used on FL-500, FL-1000 FL-Imagers.



PL-55BL/120 or 230
Replacement electronic ballast for PL-55W fluorescent tube. Used on FL-stripe.



PL-55W
Replacement fluorescent tube for FL-Stripe, 55W T-5 tube, 5200K



PL-75W
Replacement fluorescent tube for FL-CircleM, FL-CircleT, and FL-CircleV.



PL-75BL/120 or 230
Replacement electronic ballast for PL-75W circular fluorescent tube. Used on CircleM, CircleV 75W circle light, completed with spiral cord, casing and belt clip. US or European power cord is included

AD-G63-E27

2 ea. of Ceramic E-27 adapter for two JCD halogen bulb to use on E-27 socket. Max. 650W.



AD-300W-E27

Set of 300W halogen bulb with E-27 adapter



AD-650W-E27

Set of 650W halogen bulb with E-27 adapter



JCD-300

2 pin type 300W halogen bulb, 3200K



JCD-650

2 pin type 650W halogen bulb, 3200K



JCD-1000

Quartz Halogen bulb, 2 pin type, 1000W 3200K



JDD250FR



Ultra bright, 3200K, 250w quartz halogen bulb with tungsten filament. Average life is 100 hours, fits on all E-27 screw base, ceramic socket. It is used widely on our F, Q, and QF Imager series lampheads. Bulb life can be extended if used on our lampheads with dimmers.

Halogen bulbs, Spiral fluorescent bulbs, Electronic ballast, have 120V and 230V version.




QF-001

QF-001A Flash protective cap
QF-001B MH Lamp protective cap



QFH-120

Wide angle reflector to use with umbrella 120 degree




QFH-12

Softbox Ring for our softbox and other make softboxes



QFH-65 QFH-65M

Standard reflector 21cm, 65 degree, Standard satin finish. QFH-65M, Mirror finish.




QFH-90

Large reflector 40cm / 16in. diameter, 90 degree w/soft diffuser




QF-003

Conical Snoot comes with 2 honey cone grid



QF-15G QF-34G

Honey cone grid 25 degree and 35 degree




QFH-4BD

4 leaf Barndoors for QFH-65 w/magnetic filter holder




QF-004

Optical snoot, with color gel, pattern disc., focusable lens.




Polyfoam board with swivel holder set



QF-7C

7 color filter, polycarbonate 280 degree, 8.25x8.25"



FL-POL1 10.5x10.5"
FL-PLL2 12.5x12.5"

Polarizing filter 150 degree
FL-POL1-polarizing filter for FL-500 10.5x10.5"
FL-POL2-Polarizing filter for Q-30 12.5x12.5"




QF-65WM

QF-65WM protective wire mesh shield for QFH-65 reflector



10-900 90/36in. umbrella
10-1060 1060/42in. umbrella
S/B=Silver/Black
W/B=White/Black
G/B=Gold/Black w/Backing
T=Translucent



40-4001QF 60x60/15x19in.
40-4002QFH 60x60/2x2ft.
40-4003QFH 90x90/3x3ft.
QFH-12 Softbox ring included

QF-7C Filter set for QFH-4BD barndoor



30-113W Carrybag w/wheels size L90xW26xH28cm for 3 flash units plus 3 stands, softboxes, umbrellas cables.



30-115
L.89
W.38
D.27cm

30-114W
L.79
W.30
D.24cm



C-21CS, Q40CS Polycarbonate Clear shield, protection from bulb shattering, can put diffuser over it, allows heat to escape, easy to attach on reflector.

Pro carrybag, extra heavy-duty, has adjustable padded dividers for stands and lights. Designed to be able for airline check-in. Ball bearing wheels.

30-114 Holds 2 stands, 2 lights
30-115 Holds 3 stands, 3 lights



40-RU85 (85cm)
40-RU105 (105cm)
Round Umbbox, opens/folds up like umbrella.



40-1M Round Softbox with ring and internal diffuser, front diffuser. Size: 1meter/40" dia.



QFH-65FS

8" fresnel spot attachment for Imagers. It is focusable by means of sliding rod. Variable angle from 5-10 degree. Unit comprises a QFH-65M reflector, 8" fresnel lens, lens barrel and sliding rod. Lens is color corrected. Accept optional barndoor and color gels



New, at Photokina 2008